

Rotoserve

Bringing The Theatre Of Rotisserie Closer To Your Customer



Rotoserve

Bringing the theatre of rotisserie closer to your customer

Global Foodservice Solutions introduce Rotoserve, the unique, theatre rotisserie display manufactured by Counterline.

This new and exclusive counter creates the perfect environment for merchandising moist, tasty, freshly cooked product with ease and simplicity.



Rotoserve Features

- Perfect for merchandising freshly cooked product such as chicken, flavoured portions, pies and ribs.
- Attractively designed to enhance customers buying experience.
- **Rotoserve** brings a unique style of theatre rotisserie closer to your customer to enhance sales.
- Energy saving - **Rotoserve** will run on a 13 amp supply.
- Continuous basting process ensures the product stays moist. The result - juicy, crispy and delicious product.
- Operated by simple, easy to use electronic controls.
- All shelves are easily removable for cleaning.
- Fully illuminated theatre with attractive curved glass for maximum customer attraction.
- Rear work shelf with built in bag holder and utensil holder.
- Under storage fat collection bin - enough capacity for a full day trading.
- Additional ambient under-counter storage space.
- Three-piece rotor system.



Rotoserve - A rotisserie theatre display counter WITHOUT the heat, labour, hygiene and cleaning issues of a rotisserie oven.

- Large panoramic window for display of product inside. **45% more vision** than a rotisserie oven.
- No more burnt-on grease on the glass.
- Much easier to clean than a rotisserie oven. Far less labour is required to clean the unit, which saves time and money.
- Quickly and easily dismantled for end of trading day cleaning.
- With holding temperatures far less than the normal 180-200°C used in a rotisserie oven, no carbon build up occurs, thus making the unit visually more attractive throughout the trading day.



Aesthetic styling, ergonomic design, high performance

The result - juicy, crispy and delicious product

Rotoserve

Unit Specifications

Overall Unit Dimensions

- 1197 mm (L) x 1218 mm (D) x 1361 mm (H)

Electrical Requirements

- 10 amp
- Available in single phase & three phase
- Wattage - 2.3 kw

Capacity

- 24 medium sized or 16 large sized chickens

Unit Weight

- 240 Kg's

Packaging Specifications

Packing Case External Dimensions

- 1360 mm (L) x 1410 mm (D) x 1550 mm (H)

Packing Case Weight

- 100 Kg's

Overall Weight (Packing Case + Unit Weight)

- 340 Kg's

